

SAFETY DATA SHEET

As of date: 2018

1. Identification

Product identifier Vison 38 LFT

Other means of identification None.

Recommended use Tile adhesive.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company name
Vison Tech Products, LLC.

Address
6464 Cunningham road
Houston, Texas 77041

Telephone number (832) 850-6085 **Fax** (281) 258-4114

Contact name Son Le

Website www.visontechproducts.com

Emergency Number (832) 850-6085

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2 (Lung)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. May cause damage to organs (Lung) through

prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after

handling. Contaminated work clothing must not be allowed out of the workplace.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Vison Porcelain SDS 1/7

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Quartz	14808-60-7	40-60
Portland Cement	65997-15-1	20-40

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. If skin irritation or rash occurs: Seek medical attention. Wash contaminated clothing before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Use fire-extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

During fire, hazardous combustion products are released that may include: Carbon oxides (COx).

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust from the spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing

Vison Porcelain SDS 2 / 7

Methods and materials for

containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or vacuum material and place in a disposal container. Dispose of unwanted material properly in accordance with all local, regional, national and international regulations.

Environmental precautions

Avoid discharge into drains, water course or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with eye, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form		
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.		
,		15 mg/m3	Total dust.		
US. OSHA Table Z-3 (29 CF	[:] R 1910.1000)				
Components	Туре	Value	Form		
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf			
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.		
		0.1 mg/m3	Respirable.		
		2.4 mppcf	Respirable.		
US. ACGIH Threshold Limi	t Values				
Components	Туре	Value	Form		
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.		
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.		
US. NIOSH: Pocket Guide	to Chemical Hazards				
Components	Туре	Value	Form		
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.		
Quartz (CAS 14808-60-7)	TWA	10 mg/m3 0.05 mg/m3	Total Respirable dust.		
ological limit values posure guidelines	No biological exposure limits noted for the ingredient(s). Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.				
propriate engineering ntrols	Good general ventilation should be used. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.				
	If exposure limits have not been established, suitable respiratory protection should be worn and Use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits				

Vison Porcelain SDS 3 / 7

Individual protection measures, such as personal protective equipment

Eye/face protection

Skin protection

Wear safety

glasses

with

side

shields

or

goggles

Hand protection

Wear protective gloves.

Skin protection

Wear chemical resistant clothing.

Other

Respiratory protection Wear a dust mask if an exposure limit is exceeded, or when dust causes discomfort or irritation.

Thermal hazards Not available.

General hygiene considerations

Periodically wash affected areas contacted by dry or wet cement products with a pH neutral soap. When using, do not eat, drink, or smoke. Wash again at the end of work. If clothing becomes saturated with wet cement products, it should be removed and replace with clean dry clothing.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Powder
Color Gray/white.
Odor Odorless.
Odor threshold Not available.
PH Not available
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit – lower (%) Not available.

Flammability limit – upper (%) Not available.

Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressureNot available.Vapor densityNot available.

Relative density 2.5

Solubility (ies)

Solubility (water) Miscible.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

VOC (Weight %) 0%

Vison Porcelain SDS 4 / 7

10. Stability and reactivity

Reactivity Chemical The product is stable and non-reactive under normal conditions of use, storage and transport.

stability Possibility of Material is stable under normal conditions.

hazardous No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Contact with incompatible materials. Moisture.

Incompatible materials Powerful oxidizers. Chlorine. Mineral acid.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may cause respiratory tract irritation. Cause damage to organs through prolonged or

repeated exposure.

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Eye contact Ingestion

characteristics

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Symptoms related to the Swallowing may cause gastrointestinal irritation.

physical, chemical and toxicological

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause respiratory irritation. May cause an allergic skin reaction.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer by inhalation of dust.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

May cause damage to organs (Lung) through prolonged or repeated exposure.

repeated exposure

Vison Porcelain SDS 5 / 7

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous.

Persistence and degradability

Bioaccumulative potential

Mobility in soil

Other adverse effects

No data available.

No data available.

Not available.

13. Disposal considerations

Disposal instructions

Dispose of contents/container in accordance with local/regional/national/international

regulations. Do not contaminate ditches or waterways with chemicals or used container.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container

is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

SARA 313 (TRI reporting)

Not regulated.

Vison Porcelain SDS 6 / 7

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

16. Other information, including date of preparation or last revision

Issue date 16-April-2018

Revision date - 01

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings



Disclaimer

The information provided is without warranty, representation, inducement or license of any kind; except that it is accurate to the best of company knowledge, or obtained from sources believed by the company to be accurate.

Vison Porcelain SDS 7 / 7